

## Technical Data

Product: RUVAC WHU 7000  
Part No.: 155162

Inlet connection:	DN 320 ISO-K	
Outlet connection:	DN 160 ISO-K	
Nominal pumping speed		
at 50 Hz:	7.000 m <sup>3</sup> /h	4.123 cfm
at 60 Hz:	8.400 m <sup>3</sup> /h	4.948 cfm
at 70 Hz:	9.800 m <sup>3</sup> /h	5.772 cfm
Pumping speed with backing pump DRYVAC DV 650:		
at 50 Hz:	4.700 m <sup>3</sup> /h	2.768 cfm
at 60 Hz:	5.300 m <sup>3</sup> /h	3.122 cfm
at 70 Hz:	5.800 m <sup>3</sup> /h	3.416 cfm
Pumping speed with backing pump DRYVAC DV 650 + RUVAC WH 2500		
at 50 Hz:	5.700 m <sup>3</sup> /h	3.357 cfm
at 60 Hz:	6.800 m <sup>3</sup> /h	4.005 cfm
at 70 Hz:	7.800 m <sup>3</sup> /h	4.594 cfm
Ultimate total pressure:	upon request	
Max. permissible pressure difference		
at 50 Hz:	20.0 - 30.0 mbar	15.0 - 22.5 Torr
at 60 Hz:	14.0 - 21.0 mbar	10.5 - 15.8 Torr
at 70 Hz:	11.0 - 14.0 mbar	8.3 - 10.5 Torr
Leak rate:	≤ 1.0 x 10 <sup>-5</sup> mbar l/s	
Operating fluid:	LEYBONOL LVO 210	
Operating fluid capacity bearing chamber:	4.75 l	5.0 qt
Noise level:	< 63 dB(A)	
Cooling water consumption:	60 - 180 l/h	
Permissible cooling water pressure:	2 - 6 bar	
Permissible cooling water temperature:	+5 to +35°C	+41 to +95°F
Cooling water connections:	G 1/4", inside thread	

## Technical Data

Product: RUVAC WHU 7000  
Part No.: 155162

Mains connection:	3-ph, 360-440 V, 50 Hz 3-ph, 410-500 V, 60 Hz	
Motor rating:	18.5 kW	24.8 HP
Idle mode power consumption		
at 50 Hz:	1.2 kW	1.6 HP
at 60 Hz:	1.4 kW	1.9 HP
at 70 Hz:	2.0 kW	2.7 HP
Nominal rotation speed		
at 50 Hz:	3.000 min <sup>-1</sup>	3.000 rpm
at 60 Hz:	3.600 min <sup>-1</sup>	3.600 rpm
at 70 Hz:	4.200 min <sup>-1</sup>	4.200 rpm
Min. permissible rotation speed:	1.200 min <sup>-1</sup>	1.200 rpm
Max. permissible rotation speed:	4.200 min <sup>-1</sup>	4.200 rpm
Motor protection rating:	IP 55	
Admissible ambient temperature:	+5 to +40°C	+41 to +104°F
Dimensions:	see dimension sheet	
Weight:	≈ 715 kg	≈ 1.578 lbs

Technical data are subject to change